



## Miniport Receiver EB200

Portable monitoring from 10 kHz to 3 GHz

- Ergonomic design for on-body operation
- Continuous frequency range 10 kHz to 3 GHz
- Detection of unlicensed transmitters
- Location of close-range to medium-range targets with the aid of Handheld Directional Antenna HE200
- Digital IF section with 12 bandwidths (150 Hz to 150 kHz)
- Fast, accurate level indication across 110 dB dynamic range
- Scanning modes
  - Frequency scanning
  - Memory scanning
- Frequency spectrum (option)
- IF panorama display (option)
- Remote-controllable via RS232 CPPP or LAN (Ethernet 10Base-T)




**ROHDE & SCHWARZ**

## Brief description

Miniport Receiver EB200 with Active Directional Antenna HE200 is a portable unit for radiomonitoring in the wide frequency range from 10 kHz to 3 GHz. Whether used for monitoring

In case of power supply interruption, all the data is stored. Operation can thus be resumed immediately after the power supply is restored.

- Location of close-range to medium-range targets with the aid of Hand-held Directional Antenna HE200
- Detection of undesired emissions including pulsed emissions
- Detection of unlicensed transmitters communicating illegally or interfering with licensed transmission



emissions, detecting interference or locating mini-transmitters irrespective of their position, EB200 offers features unrivalled in its class. The favourably priced and compact receiver with LAN interface may also be used in computer-based stationary systems.

The EB200 is characterized by high input sensitivity and frequency setting accuracy throughout the frequency range from 10 kHz to 3 GHz.

Its small dimensions and low weight as well as a sturdy, pickup-proof die-cast aluminium housing with well-protected integrated operating elements make the EB200 ideal for use in places which cannot be reached with a vehicle. Its low power consumption permits battery operation typically of four hours. The EB200 battery pack is easily accessible and can be exchanged quickly.

EB200 fulfils the following tasks:

- Monitoring of given frequencies, eg storage of 1 to 1000 frequencies, squelch setting, constant monitoring of one frequency or cyclical scanning of several frequencies
- Searching in a frequency range with freely selectable start and stop frequency and step widths of 1 kHz to 9.999 MHz

- Protection against tapping by detecting miniature spy transmitters (bugs)
- Monitoring of one's own radio exercises in a service band
- Monitoring of selected transmissions
- Remote-controlled operation via modem and PC in coverage measurement and monitoring systems

EB200 and HE200: ergonomic design for on-body operation



## Digital IF section

The EB200 covers the wide frequency range from 10 kHz to 3 GHz. Processing all signals available with optimum signal-to-noise ratio requires a large number of IF bandwidths. This problem cannot be solved by means of analog filters as space is limited. The solution is a digital IF section in which a wide variety of different filters can be implemented in a relatively small space with the aid of DSP. The EB200 has 12 IF bandwidths between 150 Hz and 150 kHz. The following digital demodulators are available: AM, FM, LSB, USB and CW. If the receiver is fitted with the IF panorama option, the number of bandwidths is increased to 15 up to 1 MHz. Bandwidths over 150 kHz are for level and deviation measurement as demodulation is not possible.

## Scanning modes

### Frequency scanning

It is possible to define a frequency range to which a complete data set can be allocated. In addition to receiver settings, the following scan parameters may be included in the data set:

- Step width
- Signal threshold (dBµV)
- Dwell time (s)
- Hold time (s)
- Signal-controlled continuation
- Suppression (individual frequencies or search ranges)

### Memory scanning

The EB200 uses 1000 definable memory locations. A complete data set, such as frequency, mode of demodulation, bandwidth, squelch level, etc., can be assigned to each memory location. The memory content can be edited or overwritten with the results of


a scanning run. The content of any memory location can be transferred to the receiver manually using the RCL key, by turning the setting knob or automatically by activating the memory scanning process.

### Frequency spectrum


Fitted with the frequency spectrum (DIGI-Scan) option, EB200 scans the frequency range of interest with digital control and displays the associated spectrum. Emissions detected can be seen at a glance. Aural monitoring of the information is possible by simply pressing a softkey. EB200 then goes to the DIGI-Scan listen mode. The stored spectrum is displayed in the background, and the emission of interest can be selected and monitored by marking it with the frequency cursor.

Location of miniature transmitters at close range is possible in the differential mode of the DIGI-Scan option. In this mode, the displayed spectrum is stored as a reference. Current spectra are superimposed on the reference


spectrum, and any new signals or variations in signal strength are clearly discernible as peaks. If the measurement is made with the distance, the field strength of transmitters at close range varies to a greater extent than that of transmitters located far away. This differential display ensures fast and reliable location of miniature transmitters even in case of spread-spectrum transmission.



DIGI-Scan: Scan mode ...




... listen mode ...




... differential mode






Overview



IF panorama



Level (zoomed)

For every task  
the optimized view ...

## State-of-the-art design

The receiver is designed for both mobile and stationary operation. Careful screening and filters in all the input and output lines guarantee extremely low spurious as well as high interference rejection.

## BITE

The receiver is permanently monitored by built-in test equipment. If deviations from the nominal are detected, an error message is output with a code informing on the type of fault.

## Serviceability

Modern design and the use of plug-in modules guarantee short repair times. All the modules may be exchanged without any recalibration or adjustments being required.

## Remote control

All the receiver functions can be remote-controlled via the serial RS232C interface of a controller. For measurement tasks, the LAN option provides a hundred times faster speed as well as easy connection and control of multiple receivers from a PC. With these different versions the user can select the type of remote control to suit his tasks.

## Function

The EB200 is a superhet receiver with a third intermediate frequency of 10.7 MHz. In spite of its compact size, it was possible to implement an advanced receiver concept. The receiver input is equipped with a high-pass/lowpass combination or tracking preselection, as required, to reduce the signal sum load. Intermodulation suppression equals that of many receivers used in stationary applications.

The low degree of oscillator reradiation is a result of large-scale filtering. A modern synthesizer concept featuring very low phase noise permits switching times of less than 3 ms. Effective frequency and memory scanning is thus possible.

## Operation

The operational concept of the EB200 meets all the requirements of a modern radiomonitoring receiver, ie all the essential functions, such as modes of demodulation, bandwidths, etc, can be set via labelled keys directly.

Settings that are not used during current operation are available in sub-menus. The hierarchy of menu control is implemented according to priorities for ease of use.



# Handheld Directional Antennas


HE200HF



HE200



▼  
▼  
▼



## Uses

The handy and highly broadband Active Directional Antenna HE200 in conjunction with portable receivers (eg EB200) is ideal for locating transmitting and interfering sources. The direction is found by pointing the antenna towards the direction of maximum signal voltage. The overall frequency range from 0.01 MHz to 3000 MHz is covered by 4 exchangeable broadband antenna modules each with a distinct directional pattern. A low-noise broadband amplifier may be added to increase sensitivity in the active mode. The amplifier is bypassed in the passive mode and in this case the antenna may also be used in the vicinity of strong transmitters.

## Description

A broadband cardioid directional pattern is obtained in the frequency ranges 20 MHz to 200 MHz and 200 MHz to 500 MHz by using a loaded loop antenna in two different sizes. A log-periodic dipole antenna covers the range 500 MHz to 3000 MHz with a directional pattern. A loop antenna is available as an option for the lower frequency range of 0.01 MHz to 20 MHz.

The four RF modules can be exchanged by means of a quick-release catch provided at the supply and display unit. The supply and display unit comprises the following modules:

- Unambiguous direction finding\*), ie directional pattern with the receive maximum pointing to the front in the frequency range 20 MHz to 3 GHz
- The maximum of the antenna output signal serves as a direction criterion (maximum direction finding)
- Handy size despite very wide broadband characteristic
- Weight is kept to a minimum due to material used and antenna design
- Can be used for vertically and horizontally polarized signals in the frequency range 20 MHz to 3 GHz
- Wide dynamic range due to switchable passive and active mode

\*) For the unambiguous determination of the angle of incidence of a signal, at least two different sites are required. The transmitter is to be located at the intersection point of the DF beams.


- Antenna electronics made up of low-noise amplifier as well as active/passive switchover circuit
- Active/passive switchover by means of relay

The low-noise amplifier is bypassed in passive mode and has no supply voltage. Passive mode is thus also possible without batteries and external voltage supply. The antenna should only be switched to active mode if there are no strong transmitters in close vicinity and if the sensitivity of the receiving system (antenna with receiver) in the passive mode is not sufficient to detect the signal. When the amplifier is activated, a yellow LED on the rear of the supply and display unit indicates whether the supply voltage from battery or external source has fallen below the permissible range.


## Specifications

|  |  |  |   |
|--|--|--|---|
| <b>Frequency range</b><br>Frequency setting<br>via keypad or rollkey   | 10 kHz to 3 GHz  | AF output, balanced<br>Loudspeaker output<br>Headphones output<br>Output log. signal level | 600 $\Omega$ , 0 dBm<br>8 $\Omega$ , 500 mW<br>via volume control<br>0 V to +4.5 V  |
| Frequency accuracy<br>Aging<br>Synthesizer setting time<br>Oscillator phase noise  | 1 kHz, 100 Hz, 10 Hz, 1 Hz or in<br>selectable increments<br>$\leq \pm 1.5 \times 10^{-6}$ ( $-10^\circ\text{C}$ to $+55^\circ\text{C}$ )<br>$\leq \pm 0.5 \times 10^{-6}$ /year<br>$\leq 3$ ms<br>$\leq -100$ dBc/Hz at 10 kHz offset | <b>BITE</b>  | monitoring of test signals by means of<br>loop test   |
| <b>Antenna input</b>   | N socket, 50 $\Omega$ , VSWR $\leq 3$ ; SMA con-<br>nector for rackmounting at rear panel  | <b>Data interface</b><br>Option  | RS232 C PPP<br>LAN (Ethernet 10Base-T)  |
| Oscillator reradiation<br>RF attenuation<br>Input selection  | $\leq -107$ dBm<br>30 dB, man. or autom., switchable   | <b>General data</b>  | Operating temperature range<br>Rated temperature range<br>Storage temperature range<br>Humidity<br>Shock  |
| 100 kHz to 20 MHz<br>20 MHz to 1.5 GHz<br>1.5 GHz to 3 GHz   | highpass/lowpass<br>tracking preselection<br>highpass/lowpass  |  | $-10^\circ\text{C}$ to $+55^\circ\text{C}$<br>$0^\circ\text{C}$ to $+50^\circ\text{C}$<br>$-40^\circ\text{C}$ to $+70^\circ\text{C}$<br>max. 95%, cyclic test 25/55°C<br>to DIN IEC 68-2-27<br>(MIL-STD-810D, MIL-T-28800D), 40 g,<br>shock spectrum 45 Hz to 2 kHz<br>to DIN IEC 68-2-6 (MIL-T-28800D),<br>5 Hz to 55 Hz, 0.15 mm amplitude<br>to DIN IEC 68-2-36, 10 Hz to 500 Hz,<br>1.9 g (rms) |
| <b>Interference rejection, nonlinearities</b>  |  | Vibration (sinewave)   | Vibration (noise)   |
| Image frequency rejection<br>IF rejection<br>2nd order intercept point<br>3rd order intercept point<br>Internal spurious signals | $\geq 70$ dB, typ. 80 dB<br>$\geq 70$ dB, typ. 80 dB<br>typ. 40 dBm<br>typ. 2 dBm<br>$\leq -107$ dBm   | Electromagnetic compatibility (EMC)  | EN50081/82-1,82-2, MIL-STD-461,<br>CE03; RE02 and RS03  |
| <b>Sensitivity</b>   |  | Power supply   | battery pack (typ. 6 h operation) or<br>DC 10 V to 30 V (max. 22 W)   |
| Overall noise figure<br>(including AF section)   |  | Dimensions (W x H x D)   | 210 mm x 88 mm x 270 mm<br>$\frac{1}{2}$ 19" x 2 HU   |
| 20 MHz to 650 MHz<br>650 MHz to 1500 MHz<br>1500 MHz to 2700 MHz<br>2700 MHz to 3000 MHz   | $\leq 14$ dB, typ. 12 dB<br>$\leq 15.5$ dB<br>$\leq 14$ dB, typ. 12 dB<br>$\leq 15$ dB, typ. 13 dB   | Weight (without battery pack)<br>Battery pack  | 4 kg<br>1.5 kg  |
| Signal-to-noise ratio  | measurement with telephone filter to<br>CCITT  | <b>Directional antennas HE200/HE200HF</b>  |   |
| AM, bandwidth 6 kHz,<br>$f_{\text{mod}} = 1$ kHz, $m = 0.5$  | $\geq 10$ dB<br>$\geq 10$ dB   | Frequency range  | 0.01 MHz to 3000 MHz  |
| 20 MHz to 2700 MHz, $V = 1$ $\mu\text{V}$<br>2.7 GHz to 3 GHz, $V = 1.3$ $\mu\text{V}$   |  | Antenna modules  | 20 MHz to 3000 MHz, with 3 plug-in<br>antennas<br>loaded loop antenna<br>loaded loop antenna<br>log-periodic antenna  |
| FM, bandwidth 15 kHz,<br>$f_{\text{mod}} = 1$ kHz, deviation = 5 kHz   | $\geq 25$ dB<br>$\geq 25$ dB   | Option   | 0.01 MHz to 20 MHz  |
| 20 MHz to 2700 MHz, $V = 1$ $\mu\text{V}$<br>2.7 GHz to 3 GHz, $V = 1.3$ $\mu\text{V}$   |  | Polarization   | loop antenna<br>vertical for all antenna modules, hori-<br>zontal polarization by turning the lon-<br>gitudinal antenna axis by $90^\circ$  |
| <b>Demodulation</b>  | AM, FM, USB, LSB, CW   | Loop antenna   | 0.01 MHz to 20 MHz  |
| IF bandwidths  | 12 (150/300/600 Hz/1.5/2.4/6/<br>9/15/30/50/120/150 kHz)   | Nominal impedance  | 50 $\Omega$   |
| IF bandwidths for level and<br>deviation indication  | 15 (150 Hz to 1 MHz) only with<br>IF Panoramic Unit EB200SU<br>signal-controlled, can be set from<br>$-10$ dB $\mu\text{V}$ to $+100$ dB $\mu\text{V}$   | SWR  | $< 2.5$ typ.  |
| Squelch  | AGC, MGC   | RF output  | 1 m cable with N connector  |
| Gain control   | 80 dB  | Gain   | for typical values see page 7   |
| IF control   | 110 dB   | Antenna factor   | for typical values see page 7   |
| RF + IF control  | digital retuning for signals unstable in<br>frequency  | Field-strength sensitivity   | for typical values see page 7   |
| AFC  | graphical with tuning label<br>graphical as level line or numerical<br>from $-10$ dB $\mu\text{V}$ to $+100$ dB $\mu\text{V}$ , acoustic<br>indication by level tone   | Linearity of amplifier   | IP3, typ. 19 dBm (battery voltage 6 V,<br>$25^\circ\text{C}$ )  |
| Deviation indication   | internal module, ranges 25, 50, 100,<br>200, 500, 1000 kHz   | Current drain  | 55 mA in active mode<br>0 mA in passive mode  |
| Signal level indication  |  | Power supply   | in handle, 4 x 1.5 V mignon cell R6   |
| IF panorama display (option SU)  |  | Dimensions (W x H x D)   | 470 mm x 360 mm x 180 mm<br>(in transport case)   |
| <b>Scan characteristics</b>  |  | <b>General data</b>  |   |
| Automatic memory scan  | 1000 definable memory locations to<br>each of which a complete data set can<br>be allocated  | Operating temperature range  | $-30^\circ\text{C}$ to $+60^\circ\text{C}$ active/passive mode  |
| Frequency scan   | START/STOP/STEP definition with<br>receiving data set  | Rated temperature range  | $-10^\circ\text{C}$ to $+50^\circ\text{C}$ active mode<br>$-30^\circ\text{C}$ to $+60^\circ\text{C}$ passive mode   |
| <b>Inputs/outputs</b>  |  | Storage temperature range  | $-30^\circ\text{C}$ to $+60^\circ\text{C}$  |
| Digital IF output  | serial data (clock, data, frame)<br>up to 256 kbps: 2 x 16 bit   | Vibration resistance   | random 10 Hz to 300 Hz: 0.01 $\text{g}^2/\text{Hz}$ ,<br>300 Hz to 500 Hz: 0.003 $\text{g}^2/\text{Hz}$ ,<br>every 30 minutes in 3 orthogonal<br>axes; acceleration approx. 1.9 g rms<br>max. 40 g, crossover frequency 45 Hz<br>in 3 orthogonal axes   |
| Bidirectional reference frequency<br>connectors  | 10 MHz, BNC  | Shock resistance   |   |
| in   | 0.1 V to 1 V; $R_i = 500$ $\Omega$   | Weights:   |   |
| out  | 0 dBm, $R_o = 50$ $\Omega$   | Supply and display unit<br>with adapters and compass                                       | 0.5 kg<br>0.65 kg   |
| I/Q output (digital)   | AF signal, 2 x 16 bit  | RF modules   |   |
| IF 10.7 MHz, wideband  | $\pm 5$ MHz uncontrolled for external<br>panoramic display   | 20 MHz to 200 MHz  | 0.55 kg   |
|  |  | 200 MHz to 500 MHz   | 0.3 kg  |
|  |  | 500 MHz to 3000 MHz  | 0.45 kg   |
|  |  | 0.01 MHz to 20 MHz   | 0.4 kg  |


Gain, passive mode




Gain, active mode




Antenna factor, passive mode




Antenna factor, active mode



Field-strength sensitivity, passive mode



Field-strength sensitivity, active mode



## Ordering information

### EB200

#### Miniport Receiver

Accessory supplied:  
power supply 110/230 V, 50/60 Hz

#### Recommended extras

|   |         |              |
|---|---------|--------------|
| Carrying Case (telescopic antenna, headset, belt and space for EB200, battery pack) | EB200SC | 4052.9304.02 |
| Battery Pack  | EB200BP | 4052.4102.02 |
| Internal IF Panoramic Unit  | EB200SU | 4052.3206.02 |
| RF Spectrum DIGI-Scan   | EB200DS | 4052.9604.02 |
| LAN Interface   | EB200R4 | 4052.9156.02 |
| Rack Adapter  | EB200ZZ | 4052.8250.02 |

### Handheld directional antennas

#### HE200

|                      |                    |              |
|----------------------|--------------------|--------------|
| HE200 comprises      | 20 MHz to 3 GHz    | 4050.3509.02 |
| Loaded loop antenna  | 20 MHz to 200 MHz  | 0701.5702.00 |
| Loaded loop antenna  | 200 MHz to 500 MHz | 0701.5354.00 |
| Log-periodic antenna | 500 MHz to 3 GHz   | 4050.3609.02 |

Accessory supplied: carrying case

#### Option HE200HF

|              |                    |              |
|--------------|--------------------|--------------|
| Loop antenna | 0.01 MHz to 20 MHz | 4051.4009.02 |
|--------------|--------------------|--------------|

Adapter and compass fitted to the supply and display unit when delivered.