

80-1000MHz/20Watts/Rack Mount

Model Number: KB0810S43A

The KB0810S43A is a rack-mountable unit incorporating a universal voltage power supply and a built in forced air-cooling system. This amplifier subsystem utilizes LDMOS power device that provides excellent power density, high efficiency, low distortion and wide dynamic range. Due to robust engineering and employment of advanced broadband RF matching networks, combining techniques and qualified components, the amplifier achieves consistent performance with field proven reliability.

FEATURES:

- Instantaneous ultra broadband
- Suitable for CW, AM, and FM modulation type
- Compact and robust design
- Standard front panel manual gain adjust

ELECTRICAL SPECIFICATIONS @ 220VAC, 25°C, 50Ω System

Parameter	Symbol	Minimum	Typical	Maximum	Units
Operating Frequency	BW	80		1000	MHz
Output Power CW	P _{SAT}		20		Watt
Power gain	PG		43		dB
Input Power for Rated P _{SAT}	P _{IN}		0		dBm
Input Return Loss	S ₁₁			-10	dB
Harmonics @ P _{OUT} =10W	H		-10		dBc
Spurious Signals	Spur		-55		dBc
Operating Voltage (1-phase)	V _{DC}		220		Volt
Power Consumption @ 20W CW	P _d			200	Watt

MECHANICAL SPECIFICATIONS

Parameter	Value	Limits
Dimensions (W x H x D) – Bench Top / Rack Mount	382.6 x 88.1x 445 mm (2U)	Max
Weight	15kg [lbs]	Max
RF Connectors Input /Output	In: Type-N, Female; Output: Type-N, Female	
Cooling	Built-in internal forced air cooling system	

ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Ambient Temperature	-10		40	°C	
Storage Temperature	-15		45	°C	
Relative Humidity (non-condensing)			95	%	

PROTECTIONS

Input RF drive level without damage	+10 dBm (Max)
VSWR protection@10W	@ 3:1- PA output power will degrade to a safe operation level, and system will still work. @ >3:1 protection will make system shutdown.

Focus on Your Application

80-1000MHz/20Watts/Rack Mount

Model Number: KB0810S43A

Thermal Overload	Power will Gracefully Degrade, when Ambient Temp >40°C
------------------	--


AVAILABLE OPTIONS (Selected options refer to the factory)

	Description	LCD
RS-232	Serial management of device /local operator access	D-Sub 9-position Male

I/O CONNECTOR-Monitor Display or RS-232

Pin#	Description	Specifications	LCD
1	Shutdown	Amplifier Disable: TTL Logic Low(<0.7V)	
2	TEMP SENSE	Analog voltage relative to temperature@10mV /°C	
3	Current Monitor	Analog voltage relative to IDD @ 100mV per Ampere	
4	Reserved	Reserved	
5	Reserved	Reserved	
6	Reserved	Reserved	
7	Reserved	Reserved	
8	Reserved	Reserved	
9	Reserved	Reserved	

OUTLINE DRAWING (All dimensions in mm)




Focus on Your Application

80-1000MHz/20Watts/Rack Mount

Model Number: KB0810S43A

TYPICAL PERFORMANCE PLOTS (For reference only)



Note:
This product will be developed upon contract/order. All the above specs are for reference only. Actual product may be different. Please check with KeyLink sales team if you have any question.