

Avionics

IFR 6000 Ramp Test Set

AEROFLEX
A passion for performance.



The IFR 6000 is a compact, lightweight and weatherproof unit designed for testing transponder modes A/C/S, TCAS I and II as well as DME.

- One main user screen for each test mode
- Detachable antenna
- Large display
- Simple user interface
- Lightweight and compact <8 lbs. (3.6 kg)
- Battery 6 hours plus duration
- Fully FAR part 43 appendix F compliant
- European Elementary and Enhanced Surveillance

The IFR 6000 features an extremely easy to use interface where every parameter the user commonly needs to view is displayed on screen.

Controls

Dedicated Mode keys for XPDR, DME and TCAS allow quick selection of the operational mode.

The application dependant softkeys and data select/slew keys provide an intuitive man machine interface.

DME mode is provided with dedicated keys for frequency/channel selection and RF level control. For frequently varied parameters in DME and TCAS modes, such as Range and Rate, dedicated keys are provided.



Operational Modes

Each operational mode has one main user screen. The operational modes are:

XPDR (Sub-Modes: ADS-B MON, ADS-B GEN & GICB)

DME

TCAS 1, 2 (Sub-Modes: TIS)

Most tests can be completed without leaving the main user screens. This simplifies the line technician's testing task.


For the very latest specifications visit

USED4TEST

Телефон: +7 (499) 685-7744

used@used4test.ru

www.used4test.ru




Mode S and ATCRBS Transponder

XPDR Auto-Test:

Every parameter the user commonly needs to view is displayed on one screen.

The auto-test performs all tests defined by FAR Part 43 Appendix F, including the proposed Eurocontrol additional tests.

The tests are tailored automatically according to reported transponder level to avoid erroneous failures.




User selects config required for test.

If the class of the transponder is unknown, the generic config may be selected which applies to the widest limits.

The test set will automatically determine the Mode S transponder level.

The selected config parameters may be displayed by pressing the INFO softkey.



Eight predetermined configs are provided to meet the currently fielded transponder test needs.




The test list is selected from the auto-test screen. This provides an easy means of selecting any of the individual tests that comprise the auto-test.

Tests on the 2nd screen (not shown) include:


- 13 UF21
- 14 UF24
- 15 ELEMENTARY SURVEILLANCE 1
- 16 ELEMENTARY SURVEILLANCE 2
- 17 ENHANCED SURVEILLANCE




The Eurocontrol Elementary Surveillance DAP's (Downlink Aircraft Parameters) are displayed on two screens.



Individual tests may be reviewed for failures which are identified by an arrow symbol.




Eurocontrol Enhanced Surveillance DAP's are displayed on one screen.





No more HEX data field interpretation!

All Mode S Format tests display parameter in engineering units.



Comprehensive II / SI code and lockout timer test




DME

All the user needs are on one screen.

- RF level control for track sensitivity tests
- Supports all DME/TACAN channels selectable in VOR paired channels
- Full UUT measured parameters are displayed.

For the very latest specifications visit



TCAS

TCAS types...

TCAS 1 MODE C

TCAS 2 ATCRBS

TCAS 2 MODE S

The Auto-Altitude feature interrogates Mode S XPDR of A/C under test to obtain current altitude.


Select pre-stored named scenarios directly from the auto-test screen.

ADS-B and GICB

ADS-B MON: Used to monitor DF17 extended squitter from transponders and DF18 extended squitter from 1090 MHz ADS-B emitters.

ADS-B GEN: Used to generate DF17/DF18 extended squitter, simulating transponders and 1090 MHz ADS-B emitters.

GICB: Used to monitor DAP's (all fields).



ADS-B MON:

The ADS-B MON LIST shows BDS formats supported.

The BDS status is annunciated to indicate if the squitter has been captured, not available or not seen.

The BDS DATA key displays the BDS DATA screen for the selected BDS number.

Transit Case:

The IFR-6000 is supplied in a rugged plastic transit case which provides stowage for the test set, directional antenna, RF coax cable, antenna shield, breakout box, and power supply/charger.



SPECIFICATION

DME MODE SPECIFICATIONS

SIGNAL GENERATOR

A 5-minute warm-up period is required for all specifications.

OUTPUT FREQUENCY

REPLY FREQUENCY

Range

962 to 1213 MHz

Accuracy

± 10 kHz

OUTPUT LEVEL

ANTENNA PORT

Range

-67 to -2 dBm at Antenna port

Resolution

1 dB

Accuracy

± 2 dB

Distance to UUT antenna

6 to 300 ft with supplied antenna

RF I/O PORT

Range

-115 to -47 dBm

Resolution

1 dB

Accuracy

-95 dBm to -47 dBm ± 1 dB

Accuracy

-115 dBm to <-95 dBm ± 2 dB

REPLY PULSE SPACING

P1 to P2

12 μ s (± 100 ns) (X Channel) @ 50% peak

P1 to P2

30 μ s (± 100 ns) (Y Channel) @ 50% peak

REPLY PULSE WIDTH

P1/P2

3.5 μ s (± 0.5 μ s)

ECHO REPLY

Control

On/Off

Position

30 nmi (± 1 nmi)

Amplitude

-11 dB (± 1 dB) relative to reply level

REPLY PULSE RISE AND FALL TIMES

ALL PULSES

Rise Time

2.5 μ s (± 0.25 μ s) (10% to 90%)

Fall Time

2.5 μ s (± 0.25 μ s) (90% to 10%)

REPLY DELAY

X CHANNEL

Fixed Reply Delay

50 μ s (± 100 ns)

Y CHANNEL

Fixed Reply Delay

56 μ s (± 100 ns)

RANGE DELAY

X AND Y CHANNEL

Range

0 to 450.00 nmi

Resolution

0.01 nmi

Accuracy

± 0.01 nmi

RANGE RATE

X AND Y CHANNEL

Range

10 to 6500 kts

Resolution

1 kts

Accuracy

$\pm 0.01\%$ typical, tested to $\pm 0.5\%$

SQUITTER

PRF

2700 Hz

Accuracy

$\pm 2\%$

Distribution

Per ARINC 568

For the very latest specifications visit

REPLY EFFICIENCY

Range

0 to 100%

Resolution

1% increments

Accuracy

±0.5%

IDENT TONE

Selection

Selectable three letter code

Frequency

1350 Hz

Accuracy

±2 Hz

UUT MEASUREMENTS

ERP

Range

+47 to +64 dBm

Resolution

0.1 dB

Accuracy

±2 dB

DIRECT CONNECTION PEAK PULSE POWER

Range

+47 to +64 dBm

Resolution

0.1 dB

Accuracy

±1 dB

FREQUENCY

Range

1025.00 to 1150.00 MHz

Resolution

10 kHz

Accuracy

±20 kHz

INTERROGATION PULSE WIDTH

P1 AND P2 PULSE WIDTHS

Range

2.00 to 5.00 μ s

Resolution

1 ns

Accuracy

±50 ns

INTERROGATION PULSE SPACING

P1 to P2 Spacing

10 to 14 μ s (X Channel)

P1 to P2 Spacing

34 to 38 μ s (Y Channel)

Resolution

10 ns

Accuracy

±20 ns

INTERROGATION PRF

Range

1 to 300 Hz

Resolution

1 Hz

Accuracy

±2 Hz

TRANSPONDER MODE SPECIFICATIONS

SIGNAL GENERATOR

RF OUTPUT FREQUENCY

Interrogation Frequency

1030 MHz

Accuracy

±10 kHz

RF OUTPUT LEVEL

ANTENNA CONNECTOR

MTL + 6 dB typical, automatically controlled for a MTL range of -83 to -68 dBm

Range

-67 to -2 dBm at antenna connector

Resolution

0.5 dB

Accuracy

±2 dB

Distance to UUT antenna

6 to 200 ft with supplied antenna

RF I/O CONNECTOR

MTL + 6 dB typical, automatically controlled

Range

-115 to -47 dBm

Resolution

0.5 dB

Accuracy

-95 to -47 dBm, ±1 dB

Accuracy

-115 to <-95 dBm, ±2 dB

ATCRBS/MODE S INTERROGATION PULSE SPACING

MODE A

P1 to P2

2.00 μ s (±25 ns)

P1 to P3

8.00 μ s (±25 ns)

MODE C

P1 to P2

2.00 μ s (±25 ns)

P1 to P3

21.00 μ s (±25 ns)

MODE S

P1 to P2

2.00 μ s (±25 ns)

P1 to P6

3.50 μ s (±25 ns)

P1 to SPR

4.75 μ s (±25 ns)

P5 to SPR

0.40 μ s (±50 ns)

INTERMODE INTERROGATION PULSE SPACING

MODE A

P1 to P3

8.00 μs (± 25 ns)

P1 to P4

10.00 μs (± 25 ns)

MODE C

P1 to P3

21.00 μs (± 25 ns)

P1 to P4

23.00 μs (± 25 ns)

INTERROGATION PULSE WIDTHS

MODE A,C,S,INTERMODE

P1,P2,P3

0.80 μs (± 50 ns)

MODE S

P6 (Short DPSK Block)

16.25 μs (± 50 ns)

P6 (Long DPSK Block)

30.25 μs (± 50 ns)

P5

0.80 μs (± 50 ns)

INTERMODE

P4 (Short)

0.80 μs (± 50 ns)

P4 (Long)

1.60 μs (± 50 ns)

INTERROGATION PULSE RISE AND FALL TIMES

ALL MODES

Rise Time

50 to 100 ns

Fall Time

50 to 200 ns

PHASE MODULATION

ALL MODES

Transition Time

≤ 80 ns

Phase Shift

180° ($\pm 10^\circ$)

SLS LEVELS

ATCRBS

SLS Level (P2)

-9 dB, -1 to +0 dB relative to P1 level

0 dB, -0 to +1 dB relative to P1 level

OFF

MODE S

SLS Level (P5)

-12 dB, -1 to +0 dB relative to P6 level

+3 dB, -0 to +1 dB relative to P6 level

OFF

Note: SLS level is automatically controlled in the SLS LEVEL test.

INTERROGATION TEST SIGNALS

MODE S

PRF

50 Hz (± 5 Hz)

ATCRBS

PRF

235 Hz (± 5 Hz)

UUT MEASUREMENTS

ERP (@ 1090 MHz)

Range

+45.5 to +59 dBm (35.5 to 800 watts)

Resolution

0.1 dB

Accuracy

± 2 dB

Direct Connection Peak Pulse Power (@ 1090 MHz)

Range

+46.5 to +59 dBm (45 to 800 watts)

Resolution

0.1 dB

Accuracy

± 1 dB

TRANSMITTER FREQUENCY

Range

1087.000 to 1093.000 MHz

Resolution

10 kHz

Accuracy

± 50 kHz

RECEIVER SENSITIVITY, RADIATED MTL

Range

-79 to -67 dBm into 0 dBi antenna

Resolution

0.1 dB

Accuracy

± 2 dB, typical

RECEIVER SENSITIVITY, DIRECT CONNECTION MTL

Range

-79 to -67 dBm

Resolution

0.1 dB

Accuracy

± 2 dB

REPLY DELAY

ATCRBS

Range

1.80 to 7.00 μs

Resolution

10 ns

Accuracy

± 50 ns

REPLY DELAY, MODE S AND ATCRBS MODE S ALL-CALL

Range

125.00 to 131.00 μ s

Resolution

10 ns

Accuracy

± 50 ns

REPLY DELAY JITTER

ATCRBS

Range

0.00 to 2.30 μ s

Resolution

1 ns

Accuracy

± 20 ns

MODE S AND ATCRBS MODE S ALL-CALL

Range

0.00 to 6.00 μ s

Resolution

1 ns

Accuracy

± 20 ns

PULSE SPACING

F1 TO F2

Range

19.70 to 21.60 μ s

Resolution

1 ns

Accuracy

± 20 ns

MODE S PREAMBLE

Range, P1 to P2

0.8 to 1.2 μ s

Range, P1 to P3

3.3 to 3.7 μ s

Range, P1 to P4

4.3 to 4.7 μ s

Resolution

1 ns

Accuracy

± 20 ns

PULSE WIDTHS

F1 AND F2

Range

0.25 to 0.75 μ s

Resolution

1 ns

Accuracy

± 20 ns

MODE S PREAMBLE

Range

0.25 to 0.75 μ s

Resolution

1 ns

Accuracy

± 20 ns

PULSE AMPLITUDE VARIATION

Range, Mode S (Relative to P1)

-3 to +3 dB

Range, ATCRBS (Relative to F1)

-3 to +3 dB

Resolution

0.1 dB (0.01 dB via RCI)

Accuracy

± 0.5 dB

DF 11 SQUITTER PERIOD

Range

0.10 to 4.88 sec

Resolution

10 ms

Accuracy

± 10 ms

DIVERSITY ISOLATION

Range

0 to >20 dB (Depending on Test Distance)

Test Distance

1.83 m (6ft) to 28.96 m (95 ft)

Resolution

0.1 dB

Accuracy

± 3 dB

TCAS MODE SPECIFICATIONS

SIGNAL GENERATOR

OUTPUT FREQUENCY

REPLY FREQUENCY

1090 MHz

Accuracy

± 10 kHz

OUTPUT LEVEL (SIMULATED ERP)

ANTENNA CONNECTOR ^{Note 1}

Radiated power at 0dBi UUT antenna

-68 dBm typical @ 10 Nmi Range, automatically controlled

Range

-67 to -2 dBm at Antenna connector

Resolution

0.5 dB

Accuracy

± 2 dB

Distance to UUT antenna

6 to 300 ft with supplied antenna

RF I/O CONNECTOR

Automatic mode

-68 dBm @ 10 Nmi Range, automatically controlled

Manual mode Range

-115 to -47 dBm

Resolution

0.5 dB

Accuracy

-95 to -47 dBm, ± 1 dB

Accuracy

-115 to <-95 dBm, ± 2 dB

REPLY PULSE SPACING

MODE C

F1 to F2

20.30 μs (± 25 ns)

F1 to C1

1.45 μs (± 25 ns)

F1 to A1

2.90 μs (± 25 ns)

F1 to C2

4.35 μs (± 25 ns)

F1 to A2

5.80 μs (± 25 ns)

F1 to C4

7.25 μs (± 25 ns)

F1 to A4

8.70 μs (± 25 ns)

F1 to B1

11.60 μs (± 25 ns)

F1 to D1

13.05 μs (± 25 ns)

F1 to B2

14.50 μs (± 25 ns)

F1 to D2

15.95 μs (± 25 ns)

F1 to B4

17.40 μs (± 25 ns)

F1 to D4

18.85 μs (± 25 ns)

MODE S

P1 to P2

1.00 μs (± 25 ns)

P1 to P3

3.50 μs (± 25 ns)

P1 to P4

4.50 μs (± 25 ns)

P1 to D1

8.00 μs (± 25 ns)

D1 to Dn (n=2 to 112)

1.00 μs times (n-1) (± 25 ns)

REPLY PULSE WIDTHS

MODE C

All Pulses

0.45 μs (± 50 ns)

MODE S

P1 through P4

0.50 μs (± 50 ns)

D1 through D112

0.50 μs (± 50 ns), 1 μs chip width

Reply Modes

TCAS I / II Mode C (with altitude reporting)

TCAS II Mode S formats 0, 11, 16

REPLY PULSE AMPLITUDES

ATCRBS

± 1 dB relative to F1

Mode S

± 1 dB relative to P1

REPLY PULSE RISE AND FALL TIMES

ALL MODES

Rise Time

50 to 100 ns

Fall Time

50 to 200 ns

PERCENT REPLY

Range

0 to 100%

Resolution

10%

Accuracy

$\pm 1\%$

REPLY DELAY

ATCRBS

3.0 μs (± 50 ns)

Mode S

128 μs (± 50 ns)

RANGE DELAY

Range

0 to 260 nmi

Resolution

0.1 nmi

Accuracy

± 0.02 nmi

RANGE RATE

Range

-1200 to +1200 kts

Resolution

10 kts

Accuracy

10%

ALTITUDE RANGE

Range

-1000 to 126,000 ft

Resolution, Mode C

100 ft

Resolution, Mode S

25 ft

ALTITUDE RATE

Range

-10,000 to +10,000 fpm

Resolution

100 fpm

Accuracy

10%

SQUITTER

Control

On/Off

Rate

0.8 to 1.2 seconds, randomly distributed

RECEIVER

PULSE SPACING

ATCRBS (Mode C All Call)

S1 to P1	2.0 μ s
Accepts	$\leq \pm 200$ ns
Rejects	$\geq \pm 1.0$ μ s
P1 to P3	21.0 μ s
Accepts	$\leq \pm 200$ ns
Rejects (<10% Replies)	$\geq \pm 1.0$ μ s
P1 to P4	23.0 μ s
Accepts	$\leq \pm 200$ ns
Rejects (<10% Replies)	$\geq \pm 1.0$ μ s

Mode S

P1 to P2	2.0 μ s
Accepts	$\leq \pm 200$ ns
Rejects (<10% Replies)	$\geq \pm 1.0$ μ s
P1 to SPR	4.75 μ s
Accepts	$\leq \pm 200$ ns
Rejects (<10% Replies)	$\geq \pm 1.5$ μ s

SUPPRESSION

ATCRBS (P2 or S1)

>0.5dB above level of P1 <10% Replies

UIUT MEASUREMENTS

ERP (@ 1030 MHz)

ATCRBS

Range

+43 to +58 dBm (20 to 631 watts)

Resolution

0.1 dB

Accuracy

± 2 dB

MODE S

Range

+43 to +58 dBm (20 to 631 watts)

Resolution

0.1 dB

Accuracy

± 2 dB

DIRECT CONNECTION PEAK PULSE POWER (@ 1030 MHz)

ATCRBS

Range

+43 to +58 dBm (20 to 631 watts)

Resolution

0.1 dB

Accuracy

± 1 dB

MODE S

Range

+43 to +58 dBm (20 to 631 watts)

Resolution

0.1 dB

Accuracy

± 1 dB

FREQUENCY

Range

1029.900 to 1030.100 MHz

Resolution

1 kHz

Accuracy

± 10 kHz

TCAS BROADCAST INTERVAL

Range

1.0 to 12.0 sec

Resolution

0.1 sec

Accuracy

± 0.2 sec

MISCELLANEOUS INPUT/OUTPUTS

RF I/O

Type

Input/Output

Impedance

50 Ω typical

Maximum Input Level

4 kW peak
10 W average

VSWR

<1.3:1

ANTENNA

Type

Input/Output

Impedance

50 Ω typical

Maximum Input Level

10 W peak
0.5 W average

VIDEO

Type

Output

Impedance

50 Ω typical

Generate Video Level

1.1 Vpp (± 0.4 V) into 50 Ω

Receive Video Level

Proportional to IF level

Baseline

± 0.5 V referenced to ground

TEST ANTENNA

VSWR

<1.5:1

Gain

6 dB, Typical

TIME BASE (TCXO)**Temperature Stability**

±1 ppm

Aging

±1 ppm per year

Accuracy

±1 ppm

Test Limit

±0.3 ppm

BATTERY**Type**

Li Ion

Duration

>4 hrs continuous operation

>6 hrs, Typical

INPUT POWER (TEST SET)**Input Range**

11 to 32 Vdc

Power Consumption

55 W Maximum

16 W Nominal at 18 Vdc with charged battery

Fuse Requirements

5 A, 32 Vdc, Type F

INPUT POWER (SUPPLIED EXTERNAL AC TO DC CONVERTER)**Input Range**

100 to 250 VAC, 1.5 A Max, 47 to 63 Hz

Mains Supply Voltage Fluctuations

≤10% of the nominal voltage

Transient Overvoltages

According to Installation Category II

ENVIRONMENTAL (TEST SET)**Use**

Pollution Degree 2

Altitude

≤4800 meters

Operating Temperature^{NOTE 2} -20°C to 55°C**Storage Temperature**^{NOTE 3} -30°C to 71°C**Relative Humidity**

95% (±5%) from 5° to 30°C

75% (±5%) from 30° to 40°C

45% (±5%) from 40° to 55°C

ENVIRONMENTAL (SUPPLIED EXTERNAL AC TO DC CONVERTER)**Use**

Indoors

Altitude

≤10,000 meters

Operating Temperature

0° to 40°C

Storage Temperature

-20°C to 71°C

PHYSICAL CHARACTERISTICS**DIMENSIONS****Height**

11.2 inches (28.5 cm)

Width

9.1 inches (23.1 cm)

Depth

2.7 inches (6.9 cm)

Weight (Test set only)

<8 lbs. (3.6 kg)

SUPPLEMENTAL INFORMATION**Test Set Certifications**

Altitude, operating	MIL-PRF-28800F	Class 2
Altitude, not operating	MIL-PRF-28800F	Class 2
Bench Handling	MIL-PRF-28800F	Class 2
Blowing Dust	MIL-STD-810F	Method 510.4, Procedure I
Drip-proof	MIL-PRF-28800F	Class 2
Explosive Atmosphere	MIL-STD-810F	Method 511.4, Procedure 1
Relative Humidity	MIL-PRF-28800F	Class 2
Shock, Functional	MIL-PRF-28800F	Class 2
Vibration Limits	MIL-PRF-28800F	Class 2
Temp, operating ^{NOTE 4}	MIL-PRF-28800F	Class 2
Temp, not operating ^{NOTE 5}	MIL-PRF-28800F	Class 2
Transit Drop	MIL-PRF-28800F	Class 2
Safety Compliance	UL-61010B-1 EN 61010-1 CSA 22.2 No 61010-1	
EMC	EN 61326	

External AC-DC Converter Certifications

Safety Compliance	UL 1950 DS CSA 22.2 No. 234 VDE EN 60 950	
EMI/RFI Compliance	FCC Docket 20780	Curve "B"
EMC	EN 61326	

Transit Case Certifications

Drop Test	FED-STD-101C	Method 5007.1 Paragraph 6.3, Procedure A, Level A
Falling Dart Impact	ATA 300	Category I
Vibration, Loose Cargo	FED-STD-101C	Method 5019
Vibration, Sweep	ATA 300	Category I
Simulated Rainfall	MIL-STD-810F	Method 506.4 Procedure II of 4.1.2
	FED-STD-101C	Method 5009.1 Sec 6.7.1
Immersion	MIL-STD-810F	Method 512.4

For the very latest specifications visit

VERSIONS AND ACCESSORIES

When ordering please quote the full ordering number information.

Ordering Numbers

Versions

6000-110	IFR 6000 Mode A/C/S Transponder and DME Ramp Test Set, with US Mains Leads
6000-220	IFR 6000 Mode A/C/S Transponder and DME Ramp Test Set, with European Mains Leads
6000OPT2	TCAS (TIS)
6000OPT3	ADS-B

Extended Standard Warranties with Calibration for 6000

W6000/203C	Extended standard warranty 36 months with scheduled calibration
W6000/205C	Extended standard warranty 60 months with scheduled calibration

Accessories for 6000

AC0820	Desk Top Stand
AC0826	Tripod
AC24006	Tripod, Dolly, Stand
AC0824CD	IFR 6000 Maintenance Manual - CD
AC0825CD	IFR 6000 Operation Manual - CD
AC0829	25ft TNC/TNC COAX
AC0830	50ft TNC/TNC COAX

Notes

NOTE 1 Simulates a 50.5 dBm XPDR ERP at 10 nMi range.

NOTE 2 Battery charging temperature range: 5°C to 40°C (controlled by internal charger).

NOTE 3 Li Ion Battery must be removed below -20°C and above 60°C.

NOTE 4 Temperature range extended to -20°C to 55°C.

NOTE 5 Temperature range reduced to -30°C to 71°C.



USED4TEST

Телефон: +7 (499) 685-7744

used@used4test.ru

www.used4test.ru