

Site Master™ S820E

Microwave Cable and Antenna Analyzer

S820E 1 MHz to 8, 14, 20, 30, and 40 GHz

The World's First Handheld 40 GHz Cable and Antenna Analyzer

The Microwave Site Master S820E is designed for installation and maintenance of microwave communication systems up to 40 GHz. Measurements and features for maximum value and productivity include:

Standard Measurements:

- 1-port measurements: Return Loss, VSWR, Cable Loss, Distance-to-Fault, Phase, and Smith Chart (50/75 Ω)*
- 2-port Transmission Measurement*
- 2-port Swept Cable Loss Measurement (external sensor required)*
- Optical connector inspection with IEC 61300-3-35 based Pass/Fail standard (requires Anritsu USB Video Inspection Probe, sold separately)*

Standard Features:

- Three year standard warranty, lowering cost of ownership
- Advanced Mode and Classic Mode (similar look and feel as the S820D)
- Line Sweep Tools for easy reporting easyTest Tools™ enables standardized testing for repeatable measurements
- Certified for use in explosive atmosphere (MIL-PRF-28800F Section 4.5.6.3)
- Optional Vector Network Analyzer Mode
- Optional Vector Voltmeter Mode with true A/B ratio measurement capability



Setting the standard for >15 years

Anritsu set the standard in 1999 with the world's first 18 GHz broadband Site Master. More than 15 years later Anritsu has set a new standard for performance and accuracy in a portable handheld analyzer with its Microwave Site Master S820E's unsurpassed coverage to 40 GHz.

Product Highlights:

1. **Broadest frequency ranges** from 1 MHz to 8, 14, 20, 30, and 40 GHz
2. **Best frequency resolution** of 1 Hz for maximum frequency flexibility
3. **Unprecedented dynamic range** of 110 dB all the way up to 40 GHz for real benchtop performance in the field
4. **Fastest sweep speed** of 550 μ s/data point for fast field measurements
5. **Highest RF immunity** of +17 dBm for operation in harsh RF environments
6. **Unsurpassed directivity** in a handheld for maximum field accuracy
7. **Largest and highest resolution display** (8.4 inch, 800x600) for maximum readability in all lighting conditions with an intuitive graphical user touchscreen interface
8. **Full temperature coax calibration kits** from -10°C to $+55^{\circ}\text{C}$ for field precision measurement
9. **Widest calibration temperature window** of $\pm 10^{\circ}\text{C}$ requiring less recalibrations
10. **Unique 2-port Swept Cable Loss Measurement** across the whole frequency range of interest in a quick one-step measurement
11. **Most popular pre-loaded waveguide calibration component coefficients** in the instrument with ten bands for SSL and SSLT calibrations making it convenient for the customer to quickly make calibrations.



*Option required on competitive products

Quick Fact Sheet

Site Master™ S820E

Microwave Cable and Antenna Analyzer

USED4TEST

Телефон: +7 (499) 685-7744
used@used4test.ru
www.used4test.ru

Anritsu
envision:ensure

Frequency Options (select one frequency option only)

| Option | Description | Ordering Number |
|------------|---|-----------------|
| Option 708 | 1 MHz to 8 GHz, type N(f) ports | S820E-0708 |
| Option 714 | 1 MHz to 14 GHz, type N(f) ports | S820E-0714 |
| Option 720 | 1 MHz to 20 GHz, type Ruggedized K(m) ports (compatible with 3.5mm & SMA) | S820E-0720 |
| Option 730 | 1 MHz to 30 GHz, type Ruggedized K(m) ports (compatible with 3.5mm & SMA) | S820E-0730 |
| Option 740 | 1 MHz to 40 GHz, type Ruggedized K(m) ports (compatible with 3.5mm & SMA) | S820E-0740 |



Phase-Stable Test Port Extension Cables (Armored and Flexible)

| Part Number | Description |
|---------------|--|
| 14RKFKF50-0.6 | 0.6 m (24"), DC to 40 GHz, Ruggedized K(f) to K(f), 50 Ω |
| 14RKFKF50-1.0 | 1.0 m (39"), DC to 40 GHz, Ruggedized K(f) to K(f), 50 Ω |
| 14RKFK50-0.6 | 0.6 m (24"), DC to 40 GHz, Ruggedized K(f) to K(m), 50 Ω |
| 14RKFK50-1.0 | 1.0 m (39"), DC to 40 GHz, Ruggedized K(f) to K(m), 50 Ω |
| 14KFKF50-0.6 | 0.6 m (24"), DC to 40 GHz, K(f) to K(f), 50 Ω |
| 14KFKF50-1.0 | 1.0 m (39"), DC to 40 GHz, K(f) to K(f), 50 Ω |
| 14KFK50-0.6 | 0.6 m (24"), DC to 40 GHz, K(f) to K(m), 50 Ω |
| 14KFK50-1.0 | 1.0 m (39"), DC to 40 GHz, K(f) to K(m), 50 Ω |
| 15NN50-1.0B | 1.0 m (39"), DC to 18 GHz, N(m) to N(m), 50 Ω |
| 15NNF50-1.0B | 1.0 m (39"), DC to 18 GHz, N(m) to N(f), 50 Ω |
| 15LL50-1.0A | 1.0 m (39"), DC to 20 GHz, 3.5 mm(m) to 3.5 mm(m), 50 Ω |
| 15LLF50-1.0A | 1.0 m (39"), DC to 20 GHz, 3.5 mm(m) to 3.5 mm(f), 50 Ω |
| 15KK50-1.0A | 1.0 m (39"), DC to 26.5 GHz, K(m) to K(m), 50 Ω |
| 15KKF50-1.0A | 1.0 m (39"), DC to 26.5 GHz, K(m) to K(f), 50 Ω |



High performance, full temperature Coaxial Calibration Kits

| Model | Frequency Range | Connector | Through | RL Specification (load) | Technical Data Sheet |
|--------------|-----------------|-----------|---------|----------------------------------|----------------------|
| OSLN50A-8 | DC to 8 GHz | N(m) | No | 6/8 GHz ≥ 42/37 dB | 11410-00733 |
| OSLNF50A-8 | DC to 8 GHz | N(f) | No | 6/8 GHz ≥ 42/37 dB | 11410-00735 |
| TOSLN50A-8 | DC to 8 GHz | N(m) | Yes | 6/8 GHz ≥ 42/37 dB | 11410-00737 |
| TOSLNF50A-8 | DC to 8 GHz | N(f) | Yes | 6/8 GHz ≥ 42/37 dB | 11410-00739 |
| OSLN50A-18 | DC to 18 GHz | N(m) | No | 6/9/18 GHz ≥ 42/37/33 dB | 11410-00734 |
| OSLNF50A-18 | DC to 18 GHz | N(f) | No | 6/9/18 GHz ≥ 42/37/33 dB | 11410-00736 |
| TOSLN50A-18 | DC to 18 GHz | N(m) | Yes | 6/9/18 GHz ≥ 42/37/33 dB | 11410-00738 |
| TOSLNF50A-18 | DC to 18 GHz | N(f) | Yes | 6/9/18 GHz ≥ 42/37/33 dB | 11410-00740 |
| TOSLK50A-20 | DC to 20 GHz | K(m) | Yes | 10/20 GHz ≥ 42/36 dB | 11410-00741 |
| TOSLKF50A-20 | DC to 20 GHz | K(f) | Yes | 10/20 GHz ≥ 42/36 dB | 11410-00743 |
| TOSLK50A-40 | DC to 40 GHz | K(m) | Yes | 10/20/30/40 GHz ≥ 42/36/32/30 dB | 11410-00742 |
| TOSLKF50A-40 | DC to 40 GHz | K(f) | Yes | 10/20/30/40 GHz ≥ 42/36/32/30 dB | 11410-00744 |

| Model Number | Description |
|--------------|--|
| MA24108A | Microwave USB Power Sensor, N(m), 10 MHz to 8 GHz, +20 dBm to -40 dBm |
| MA24118A | Microwave USB Power Sensor, N(m), 10 MHz to 18 GHz, +20 dBm to -40 dBm |
| MA24126A | Microwave USB Power Sensor, K(m), 10 MHz to 26 GHz, +20 dBm to -40 dBm |
| SC8268 | USB Transmission Sensor, K(m), 1 MHz to 40 GHz, +10 dBm to -50 dBm |
| 2000-1900-R | USB 2.0 Active 100 meter Extender (with Type A power cord for USA, Japan, North America, Central America and Caribbean) |
| 2000-1901-R | USB 2.0 Active 100 meter Extender (with Type C power cord for use in Europe, India, South Korea, and many countries in Middle East and Africa) |
| 2000-1902-R | USB 2.0 Active 100 meter Extender (with Type I power cord for use in Australia, New Zealand, Argentina, and the South Pacific) |
| 2000-1903-R | USB 2.0 Active 100 meter Extender (with Type G power cord for use in the UK, and several other countries in Asia, the Middle East, and Africa) |
| 2100-28-R | Cat 5e extension cable for use with USB Extender (22.5 m) |

Pricing | Ordering | Support